

# NVR-E16-2D

Network Video Recorder



## قابلیت های کلیدی


- یک عدد 4K HDMI و یک عدد VGA همزمان
- پشتیبانی از 2 عدد هارد تا ظرفیت 6 ترابایت برای هر کدام
- قابلیت برگرداندن تصاویر بعد از قطع شبکه
- قابلیت بروزرسانی آنلاین

- پشتیبانی از فرمت های تصویر Ultra265, H.265, H.264
- 16 کانال تصویر ورودی تا رزولوشن 8 مگاپیکسل
- پشتیبانی از دوربین های با پروتکل ONVIF

## Specifications

IP Video Input	16-ch	Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D2/1CIF/CIF
Two-way Audio Input	1-ch, RCA	Capability	1 x 4K@1,30 x 6MP@30,1 x 5MP@2,30 x 4MP@4,30 x 1080p@8,30 x 720p@30,16 x D1
Incoming bandwidth	160Mbps	SATA	2 SATA interface
Outgoing bandwidth	96Mbps	VCA Detection	Face detection, Intrusion detection, Cross Line detection, Audio detection, Human Body detection, People Counting, Scene Change detection, Defocus detection, Auto Tracking, Object Left Behind, Object Removed
Remote Users	128	VCA Search	Face Search, Behavior Search
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	Capacity	up to 6TB for each disk
HDMI/VGA Output	HDMI: 4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60	Network Interface	1 RJ45 45-M/100M/1000M self-adaptive Ethernet Interface
Audio Output	1-ch, RCA	USB Interface	Rear panel: 1 x USB2.0, Front panel: 1 x USB2.0
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Power Supply	12V DC Power Consumption: ≤ 7 W (without HDD)
Synchronous Playback	16-ch	Working Environment	-10°C--+ 55°C (+14°F--+131°F), Humidity ≤ 90% RH (non-condensing)
Corridor Mode Screen	3/4/5/7/9/10/12/16	Dimensions (W×D×H)	380mm × 315mm × 53mm (15.0" × 12.4" × 2.1")
Decoding format	Ultra265/H.265/H.264	Weight (without HDD)	≤ 1.6Kg (3.53lb)

## Dimensions



## Rear Panel