

# IPC-E2F4W-I30

4MP StarLight Vandal-resistant Network Fixed Dome Camera



## قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

## Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F1.6				
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	2.8	63	25.2	12.6	6.3
Angle of View (H)	105.3°				
Angle of View (V)	57°				
Angle of View (O)	136.9°				
Adjustment angle	Pan: 0°-360°		Tilt: 0°-68°		Rotate: 0°-360°
	Shutter				
Minimum Illumination	Colour: 0.005Lux ( F1.6, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	30-50m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile 120db				
Frame Rate	Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 2MP (1920*1080), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 25fps				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 4 areas				
Motion Detection	Up to 4 areas				
Smart Features	Human body detection				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/ Auto2				
Digital noise reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Vertical/Horizontal/180°				
Dewarping	Support				
HLC	Supported				
BLC	Supported				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below				
Edge Storage	Micro SD, up to 256 GB				
Network Storage	ANR				
Network	10/100M Base-TX Ethernet				
Certifications	CE: EN 60950-1				
	UL: UL60950-1				
	FCC: FCC Part 1				
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 3.5W				
Dimensions (Ø x H)	Ø109 x 81mm (Ø4.3" x 3.2")				
Net Weight	0.49kg (1.08lb)				
Material	Shield: PC				
	Body: plastic Bottom plate: metal				
Working Environment	-30°C - 60°C [-22°F - 140°F], Humidity: ≤95% RH (non-condensing)				
Storage Environment	-30°C - 60°C [-22°F - 140°F], Humidity: ≤95% RH (non-condensing)				
Surge Protection	2KV				
Ingress Protection	IP67				
Vandal Resistant	IK10				

## Dimensions

