



IPC-P2A8W-I30S

8MP WDR VF Vandal-resistant IR Dome Network Camera

- قابلیت روز و شب
- IR هوشمند تا 30 متر
- WDR 120 دسیبل
- کاهنده نویز دیجیتال 3D

- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16

قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- پشتیبانی از POE
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت

Specifications

Sensor	1/2", 8.0 megapixel, progressive scan, CMOS					ROI	Up to 8 areas
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens					Motion Detection	Up to 4 areas
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Smart Features	Audio detection, Cross line, intrusion, object left, object removed, people counting, Face capture
	2.8	63	25.2	12.6	6.3	Audio Compression	G.711
	12	270	108	54	27	Two-way audio	Supported
Angle of View (H)	114.8° ~ 47.3°					Suppression	Supported
Angle of View (V)	75.3° ~ 20.4°					Sampling Rate	8KHZ
Angle of View (O)	141.2° ~ 55.8°					Edge Storage	Micro SD, up to 256GB
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 80°		Rotate: 0° ~ 360°	Network Storage	ANR
Shutter	Auto/Manual, 1 ~ 1/100000s					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Minimum Illumination	Colour: 0.001Lux (F1.5, AGC ON) 0Lux with IR					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
IR Range	Up to 30m (98ft) IR range					Audio I/O	Audio cable Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
Day/Night	IR-cut filter with auto switch (ICR)					Alarm I/O	1/1
S/N	>52dB					Network	1 RJ45 10M/100M Base-TX Ethernet
Defog	Digital Defog					Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
WDR	120dB					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8W
Video Compression	Ultra 265, H.264, MJPEG					Dimensions (D x H)	Ø148 x 111.3mm (Ø5.8" x 4.4")
Frame Rate	Main Stream: 8MP (3840*2160), Max 20fps; 5MP (2592*1944), Max 30fps; 5MP (2944*1656), Max 30fps; 4MP (2560*1440), Max 30fps; 2MP (1920*1080), Max 30fps;					Weight	0.92kg (2.0lb)
	Sub Stream: 2MP (1920*1080), Max 30fps;					Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Third Stream: D1 (720*576), Max 30fps					Reset Button	Supported
9:16 Corridor Mode	Supported					Ingress Protection	IP67
HLC	Supported					Vandal Resistant	IK10
BLC	Supported						
OSD	Up to 8 OSDs						
Privacy Mask	Up to 8 areas						

Dimensions

