

IPZ-P4425W-I100S

4MP 25x Lighthunter Network PTZ Dome Camera



Network
Cameras

NVRs

Video
Decoders

Controller

Switches

Accessories


قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +70 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- بدنه ضد ضربه با استاندارد IK10
- رزولوشن 4 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 25 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق تر و سریع
- IR هوشمند تا 100 متر

Specifications

Sensor	1/2.8", 4.0 megapixel, progressive scan, CMOS				
Minimum Illumination	Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1 ~ 1/100000s				
WDR	120dB				
S/N	>56dB				
Lens type	4.8 ~ 120mm, AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	25				
Iris	Auto; F1.5 ~ F3.8				
Angle of View (H)	52.20°~2.74°				
Angle of View (V)	30.81°~1.54°				
Angle of View (D)	64.20°~3.23°				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.8	119.3(391.2ft)	47.7(156.5ft)	23.9(78.2ft)	11.9(39.1ft)
	120	2475.0(8120.1ft)	990.0(3248.0ft)	495.0(1624.0ft)	247.5(812.0ft)
IR Range	Up to 100m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 4MP(2688*1520), Max 30fps;				
	Sub Stream: 2MP (1920*1080), Max 30fps;				
	Third Stream: D1 (720*576), Max 30fps;				
Video Bit Rate	128 Kbps~16 Mbps				
ROI	Support				
OSD	Up to 8 OSDs				
Privacy Mask	24 areas, up to 4 areas per scene				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
HLC	Support				
BLC	Support				
Defog	Digital Defog				
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40), Auto Tracking				
Audio Compression	G.711U, G.711A				
Two-way Audio	Support				
Suppression	Support				
Sampling Rate	8 kHz				
Edge Storage	Micro SD, up to 256 GB				
Network Storage	ANR, NAS, NFS				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T1), API, SDK				
User/Host	Up to 32 users. 2 user levels: administrator and common user				
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below				
Pan Range	360° (endless)				
Pan Speed	0.1°/s ~ 200°/s Preset speed: 240°/s				
Tilt Range	-15° ~ 90° (auto reverse)				
Tilt Speed	0.1°/s ~ 200°/s Preset speed: 200°/s				
Number of Presets	1024				
Preset Patrol	16 patrols, up to 64 presets for each patrol				
Patrol Stay Time	15s~1800s				
Home Position	Support				
Audio I/O	1/1				
Alarm I/O	2/1				
Serial Port	1 RS485				
Network	1 * RJ45 10M/100M Base-TX Ethernet				
Video Output	1 BNC				
Power	DC12V(±25%, 3A), PoE+(IEEE 802.3at)				
Weight	Power consumption: MAX 21W 3.05kg(6.72lb)				
Working Environment	-40°C~70°C(-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	6KV				
Reset Button	Support				
Protection	Ingression protection: IP67 Vandal resistant: IK10				

Dimensions



WWW.DIESPI.IR