

IPC-E3F4D-I30/D

4MP Fixed Dome Network Camera



قابلیت های کلیدی

- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم


- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Min Illumination	Color: 0.01 Lux (F2.0 AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1 - 1/100000s				
Adjustment angle	Pan: 0° - 360°, Tilt: 0° - 75°, Rotate: 0° - 360°				
S/N	>56dB				
WDR	100dB				
Lens Type	2.8mm @2.0				
Lens Mount	M12				
Angle of View (H)	97.0°				
Angle of View (V)	52.2°				
Angle of View (D)	107.5°				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0	25.2	12.6	6.3
IR Range	30-50m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Frame Rate	Main Stream: 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps Sub Stream: 4CIF (704*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps;				
Video Bit Rate	128 Kbps-6144 kbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Smart Features	Cross Line, Intrusion detection (based on human body detection)				
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser				

Digital noise reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°
Dewarping	N/A
HLC	Supported
BLC	Supported
Defog	Digital Defog
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR, NAS/NFS
Protocols	IPV4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, SNMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSE and digest authentication for ONVIF ONVIF (Profile S, Profile G, Profile T), API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Network	1 * RJ45 10M/100M Base-TX Ethernet
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4.0W
Dimensions (Ø x H)	Ø118 x 97mm (Ø4.6" x 3.8")
Weight	0.30kg (0.66lb)
Material	Metal + Plastic
Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4kV
Reset Button	N/A
Ingress Protection	Ingress protection: IP67

Dimensions



63