

IPC-P1A4WH-I50S

4MP LightHunter Intelligent Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- Ultra265, H.265, H.264, MJPEG
- پایه قابل تنظیم 3 حالت
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- OSD قابل تنظیم
- IR هوشمند 50 تا 80 متر
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8-12mm@F1.2, AF automatic focusing and motorized zoom lens				
Iris	Fixed				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	42(137.8ft)	16.8(55.1ft)	8.4(27.6ft)	4.2(13.8ft)
Angle of View (H)	35.6°-107.9°				
	20.4°-75.4°				
Angle of View (V)	43.8°-140.3°				
Shutter	Auto/Manual, 1 ~ 1/100000s				
Min. Illumination	Colour:0.0005lux (F1.2, AGC ON) 0 lux with IR				
WDR	120dB				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
IR Range	50-80m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 4MP(2688*1520), Max 30fps; 4MP(2560*1440), Max 30fps; 2MP(1920*1080), Max 60fps				
	Sub Stream: 2MP (1920*1080), Max 60fps;				
	Third Stream: D1 (720*576), Max 60fps 128 Kbps-16 Mbps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas (8 blacks / 8 mosaics)				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
HLC	Support				
BLC	Support				

General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Smart Features	Audio detection, Scene change detection, defocus detection, object left, object removed, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40)
Audio Compression	G.711U, G.711A
Two way audio	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR, NAS(NFS)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMPSupported
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Audio I/O	Audio cable
	1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	2/1
Network	1 x RJ45 10M/100M Base-TX Ethernet
Serial Port	1 RS485
Power	DC12V(±25%), PoE+(IEEE802.3at)
	Power consumption: Max 14W Support overcurrent protection, Input short circuit protection
Dimensions (Ø x H)	Ø306,4x104,1x98,1mm@12.1"x4.1"x3.9"
Net Weight	1.65kg(3.64lb)
Material	Metal
Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Vandal Resistant	IK10
Ingress Protection	IP67
Reset Button	Supported

Dimensions

