

# IPC-P1F4W-I30 4.0 mm

## 4MP SD Card Mini Fixed Bullet Network Camera



- IR هوشمند تا 30 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز
- پشتیبانی از کارت حافظه SD

- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از حالت راهرو 9:16
- قابلیت روز و شب

- ### قابلیت های کلیدی
- پشتیبانی از پروتکل ONVIF
  - دمای کارکرد -35 تا +60 درجه سانتیگراد
  - مقاومت در برابر نفوذ آب و گرد و غبار IP67
  - پایه قابل تنظیم 3 حالت

## Specifications

sensor	1/3", 4.0 megapixel, progressive scan, CMOS					9:16 Corridor Mode	Supported
Lens	4.0mm@F2.0					HLC	Supported
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	BLC	Supported
	4.0	90	36	18	9	DSD	Up to 8 OSDs
Angle of View (H)	78.9°					Privacy Mask	Up to 8 areas
Angle of View (V)	39.6°					ROI	Up to 8 areas
Angle of View (O)	97.0°					Motion Detection	Up to 4 areas
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°		Rotate: 0° ~ 360°	Smart Features	Cross line, intrusion, object left, object removed, People Counting, Face capture
Shutter	Auto/Manual, 1 ~ 1/100000s					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Day/Night	IR-cut filter with auto switch (ICR)					Network	1 RJ45 10M/100M Base-TX Ethernet
Digital noise reduction	2D/3D DNR					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 6.5W
S/N	>52dB					Dimensions (L × W × H)	157.3 × 62.4 × 63mm (6.2" × 2.5" × 2.5")
IR Range	Up to 30m (98ft) IR range					Weight	0.45kg (0.99lb)
Defog	Digital Defog					Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
WDR	120dB					Ingress Protection	IP67
Video Compression	Ultra 265, H.265, H.264, MJPEG					Reset Button	Supported
H.264 code profile	Baseline profile, Main Profile, High Profile						
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; 4MP (2560*1440), Max 25fps;						
	3MP (2048*1520), Max 30fps;						
	Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps						

## Dimensions

