

IPZ-P6433W-I150S

4MP 33x Lighthunter Network PTZ Dome Camera



قابلیت های کلیدی

- لوکس نوری پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 150 متر

- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 33 برابر بزرگ نمایی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +70 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- رزولوشن 4 مگاپیکسل

Specifications

| | | | | | |
|-------------------------|--|-------------------|------------------|-----------------|-----------------|
| Sensor | 1/2.8", 4.0 megapixel, progressive scan, CMOS | | | | |
| Minimum Illumination | Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Shutter | Auto/Manual, 1 - 1/100000s | | | | |
| WDR | 120dB | | | | |
| S/N | >56dB | | | | |
| Lens type | 4.5 - 148.5mm, AF automatic focusing and motorized zoom lens | | | | |
| Digital Zoom | 16 | | | | |
| Optical Zoom | 33 | | | | |
| Iris | Auto; F1.5 - F4.0 | | | | |
| Angle of View (H) | 53.0° - 2.3° | | | | |
| Angle of View (V) | 31.0° - 1.3° | | | | |
| Angle of View (D) | 65.2° - 2.7° | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 4.5 | 105.8(346.9ft) | 42.3(138.8ft) | 21.2(69.4ft) | 10.6(34.7ft) |
| | 148.5 | 3172.5(10408.5ft) | 1269.0(4163.4ft) | 634.5(2081.7ft) | 317.3(1040.8ft) |
| | | | | | |
| IR Range | Up to 150m IR range | | | | |
| Wavelength | 850nm | | | | |
| IR On/Off Control | Auto/Manual | | | | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG | | | | |
| Frame Rate | Main Stream: 4MP(2688*1520), Max 30fps; | | | | |
| | Sub Stream: 2MP (1920*1080), Max 30fps; | | | | |
| | Third Stream: D1 (720*576), Max 30fps; | | | | |
| Video Bit Rate | 128 Kbps-16 Mbps | | | | |
| ROI | Up to 8 areas | | | | |
| OSD | Up to 8 OSDs | | | | |
| Privacy Mask | 24 areas, up to 4 areas per scene | | | | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 | | | | |
| Digital noise reduction | 2D/3D DNR | | | | |
| Flip | Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise | | | | |
| HLC | Support | | | | |
| BLC | Support | | | | |
| Defog | Digital Defog | | | | |
| General Function | Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication | | | | |
| Smart Features | Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40), Auto Tracking | | | | |

| | |
|------------------------|--|
| Audio Compression | 6.711U,6.711A |
| Two-way Audio | Support |
| Suppression | Support |
| Sampling Rate | 8 kHz |
| Edge Storage | Micro SD, up to 256 GB |
| Network Storage | ANR,NAS(NFS) Network |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API,SDK |
| User/Host | Up to 32 users. 2 user levels: administrator and common user |
| Security | Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF |
| Web Browser | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below |
| Pan Range | 360° (endless) |
| Pan Speed | 0.1°/s - 200°/s Preset speed: 300°/s |
| Tilt Range | -15° - 90° (auto reverse) |
| Tilt Speed | 0.1°/s - 200°/s Preset speed: 240°/s |
| Number of Presets | 1024 |
| Preset Patrol | 16 patrols, up to 64 presets for each patrol |
| Patrol Stay Time | 15s-1800s |
| Home Position | Support |
| Audio I/O | 1/1 |
| Alarm I/O | 2/1 |
| Serial Port | 1 RS485 |
| Network | 1 * RJ45 10M/100M Base-TX Ethernet |
| Video Output | 1 BNC |
| Power | AC 24V±25%, DC 24V±25%, PoE+ (IEEE802.3 at) Power consumption: Max 25W |
| Dimensions (D x H) | Ø227 x 384.8mm (Ø8.9" x 15.1") |
| Weight | 5.28kg(11.64lb) |
| Working Environment | -40°C - 70°C (-40°F - 158°F) , Humidity: ≤95% RH (non-condensing) |
| Surge protection | 6KV |
| Reset button | Support |
| Protection | Ingress Protection: IP66 Vandal Resistant: N/A |

Dimensions

