

SW-SL2-8P-2E

8-Port PoE Switch



قابلیت های کلیدی

- حالت های کاری نرمال، ایمن، نظارت تصویری
- کنترل ترافیک پورت ها
- انتقال دیتا و برق تا 250 متر در حالت نظارت تصویری

Specifications

Ports	10×100Mbps network ports (RJ45), including 8 PoE ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	2Gbps
Forwarding performance	1.49Mpps
Packet Buffer	2Mbit
MAC	8K
Dimensions (W×D×H)	220mm x 150mm x 44mm(8.7"×5.9"×1.7")
Weight	<1.22kg
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 120W Max capacity for single port: 30W
Switch Power	122W
Surge Protection	Common mode ±6KV Differential mode ±4KV
Electrostatic standard	Common mode ±6KV Differential mode ±8KV
Cooling Fans	0
Mean Time Between Failure(MTBF)	>50000 hours
Ambient temperature	0°C-45°C (32°F-113°F)

Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Indicator	PWR: Steady on: AC input is normal Off: No AC input
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data
	Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps
Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters ,also downlink ports can communicate only with uplink ports.

Dimensions

