

IPX-A1F5W-I30

5MP IR Fixed Explosion-Proof Bullet Network Camera



قابلیت های کلیدی

- OSD قابل تنظیم
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- بدنه استیل ضد زنگ 304
- Exd IIC T6 Gb/ Ex tD A21 IP68 T80°C
- پشتیبانی از ROI
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP68

Specifications

| | | | | | |
|----------------------------|---|------------|-------------|---------------|--------------|
| Sensor | 1/2.7", 5.0 megapixel, progressive scan, CMOS | | | | |
| Lens | 4mm | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 4.0mm | 90.0 | 36.0 | 18.0 | 9.0 |
| Angle of View (H) | 91.8° | | | | |
| Angle of View (V) | 46.4° | | | | |
| Angle of View (D) | 119.3° | | | | |
| Shutter | Auto/Manual, 1-1/100000 s | | | | |
| Minimum Illumination | Colour: 0.003 Lux (F1.6, AGC ON) | | | | |
| | BW: 0.002 Lux (F1.6, AGC ON) | | | | |
| WDR | 120dB | | | | |
| Iris | Auto/Manual, F1.6 | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| IR Range | 30-50m IR Range | | | | |
| S/N | >56dB | | | | |
| Video Compression | H.265, H.264, MJPEG | | | | |
| Frame Rate | Main Stream:5MP (2880*1620): Max 30 fps; | | | | |
| OSD | Up to 8 OSDs | | | | |
| Privacy Mask | 24 areas, up to 4 areas per scene | | | | |
| ROI | Up to 8 areas | | | | |
| Behavior Detection | Motion detection, Tampering Detection | | | | |
| Smart intrusion Prevention | Support false alarm filtering: Line crossing detection, Intrusion detection, Region entrance detection, Region exit detection | | | | |
| Recognition | Face capture | | | | |
| Protocols | L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, SNMP, HTTPS, SIP, RTMP | | | | |
| Compatible Integration | ONVIF, GB/T28181, IMOS, API | | | | |
| Network | 10/100M Base-TX Ethernet | | | | |
| Power | DC12V(±25%), PoE(IEEE802.3af) | | | | |
| | Power consumption: 4.3W | | | | |
| Dimensions (L x W x H) | 134 x 114 x 115 mm (5.3" x 4.5" x 4.5") | | | | |
| Weight | 2.07kg (4.56lb) | | | | |
| Working Environment | -30°C ~ +60°C (-22°F ~ 140°F), Humidity :5%-95% RH(non-condensing) | | | | |
| Ingress Protection | IP68 | | | | |

Dimensions

