

IPC-P2A4WH-I40S

4MP LightHunter Intelligent Vandal-resistant Dome Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از 5 استریم تصویر
- IR هوشمند 40 تا 70 متر
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8-12mm@F1.2, AF automatic focusing and motorized zoom lens				
Iris	Auto aperture				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	42(137.8ft)	16.8(55.1ft)	8.4(27.6ft)	4.2(13.8ft)
	12	180(590.4ft)	72(236.2ft)	36(118.1ft)	18(59.0ft)
Angle of View (H)	35.6°-107.9°				
Angle of View (V)	20.4°-75.4°				
Angle of View (O)	43.8°-140.3°				
Shutter	Auto/Manual, 1 - 1/100000s				
Adjustment angle	Pan: 0°-355°		Tilt: 0°-68°		Rotate: 0°-355
Min. Illumination	Colour:0.0005lux (F1.2, AGC ON) 0 lux with IR				
WDR	120dB				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>55dB				
IR Range	40-70m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 4MP(2688*1520), Max 30fps; 4MP(2560*1440), Max 30fps; 2MP(1920*1080), Max 60fps				
	Sub Stream: 2MP (1920*1080), Max 60fps;				
	Third Stream: D1 (720*576), Max 60fps				
	Fourth Stream: D1 (720*576), Max 60fps				
	Fifth Stream: D1 (720*576), Max 60fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas (8 blacks/8 mosaics)				
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture, (Maximum 40)				

White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise
HLC	Support
BLC	Support
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	6.711U, 6.711A
Two way audio	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR, NAS(NFS)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP
Compatible Integration	ONVIF, API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Audio I/O	Audio cable
	1 Input: impedance 35kΩ; amplitude 2V *p-p] 1 output: impedance 600Ω; amplitude 2V *p-p]
Alarm I/O	1/1
Network	1 x RJ45 10M/100M Base-TX Ethernet
	AC24V±25%, DC12V(±25%), PoE(IEEE 802.3af)
Power	Power consumption: Max 10W
	Support overcurrent protection, Input short circuit protection
Dimensions (Ø x H)	Ø148 x 111.3mm(Ø5.8" x 4.4")
Net Weight	0.96kg(2.12lb)
Material	Metal
Working Environment	-30°C-60°C(-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Vandal Resistant	IK10
Ingress Protection	IP67

Dimensions

