

IPZ-A8440W-I250SF

4MP 40X Lighthunter IR Network PTZ Dome Camera



قابلیت های کلیدی

- لوکس نوری بسیار پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 250 برابر
- طلق ضد بازتاب نور مادون قرمز
- رزولوشن 4 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 40 برابر بزرگ نمایش
- پشتیبانی از پروتکل ONVIF
- طراحی مؤثر دفع گرما
- تکنولوژی کنترل دمای هوشمند
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- PoE++(IEEE 802.3bt)

Specifications

Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS				
Minimum Illumination	Colour: 0.0005Lux (F1.3, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1 - 1/100000s				
WDR	120dB				
S/N	>56dB				
Lens type	5.7 - 228mm, AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	40				
Iris	Auto; F1.3 - F4.6				
Angle of View (H)	59.5° - 2.2°				
Angle of View (V)	35.6° - 1.2°				
Angle of View (D)	73.2° - 2.6°				
DDRI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	5.7	107.2(351.8ft)	42.9(140.7ft)	21.4(70.4ft)	10.7(35.2ft)
IR Range	228	3330.6(10927.2ft)	1332.2(4370.9ft)	666.1(2185.4ft)	333.1(1092.7ft)
	Up to 250m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Frame Rate	Main Stream: 4MP (2688*1520), Max 30fps;				
	Sub Stream: 2MP (1920*1080), Max 30fps;				
	Third Stream: D1 (720*576), Max 30fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Up to 8 areas				
OSD	Up to 8 OSDs				
Privacy Mask	24 areas, up to 4 areas per scene				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
EIC	Support				
HLC	Support				
BLC	Support				
Defog	Optical Defog & Digital Defog				
Smart Features	Deep learning, Smart intrusion Prevention Line Crossing, intrusion detection, Region entrance detection, Region exit detection, People flow counting and Crowd density monitoring, Face Capture (Maximum 40), Auto tracking (Deep learning), Audio Detection				
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Audio Compression	G.711U, G.711A				
Audio Bitrate	64 Kbps				

Two-way audio	Support
Suppression	Support
Sampling Rate	8 kHz
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
User/Host	Up to 32 users, 2 user levels: administrator and common user
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Pan Range	360° (endless)
Pan Speed	0.1°/s - 180°/s Preset speed: 300°/s
Tilt Range	-15° - 90° (auto reverse)
Tilt Speed	0.1°/s - 180°/s Preset speed: 240°/s
Number of Presets	1024
Preset Patrol	16 patrols, up to 64 presets for each patrol
Route Patrol	16 patrols, up to 32 actions for each patrol
Recorded Patrol	16 patrols, up to 128 actions for each patrol
Patrol Stay Time	15s-1800s
Preset Image Freeze	Support
Home Position	Support
Audio I/O	1/1
Alarm I/O	7/2
Serial Port	1 RS485
Network	1*100M/1000M Base-FX SFP + 1*10M/100M Base-TX Ethernet
Video output	1 BNC
Power	AC 24V ±25%, DC 24V±25%, PoE++ (IEEE 802.3bt) Power consumption: Max 61W
Dimensions (Ø x H)	Ø270 x 497mm (Ø10.6" x 19.6")
Weight	9.5kg(20.9lb)
Working Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Reset Button	Support
Protection	Ingress Protection: IP66 Vandal Resistant: N/A

Dimensions

