IPZ-P6433W-I150S

4MP 33x Lighthunter Network PTZ Dome Camera

قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد 40- تا 70+ درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- رزولوشن 4 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 33 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 150 متر

Specifications

Sensor	1/2.8", 4.0 megapixel, progressive scan, CMOS
Minimum Illumination	Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
WDR	120dB
S/N	>56dB
Lens type	4.5 ~ 148.5mm, AF automatic focusing and motorized zoom lens
Digital Zoom	16
Optical Zoom	33
Iris	Auto; F1.5 ~ F4.0
Angle of View (H)	53.0° ~ 2.3°
Angle of View (V)	31.0° ~ 1.3°
Angle of View (D)	65.2° ~ 2.7°
DORI Distance	Lens (mm) / Detect (m) / Observe (m) / Recognize (m) / Identify (m) 4.5 / 105.8(346.9ft) / 42.3(138.8ft) / 21.2(69.4ft) / 10.6(34.7ft) 148.5 / 3172.5(10408.5ft) / 1269.0(4163.4ft) / 634.5(2081.7ft) / 317.3(1040.8ft)
IR Range	Up to 150m IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	Main Stream: 4MP(2688*1520),Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps;
Video Bit Rate	128 Kbps~16 Mbps
ROI	Up to 8 areas
OSD	Up to 8 OSDs
Privacy Mask	24 areas, up to 4 areas per scene
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise
HLC	Support
BLC	Support
Defog	Digital Defog
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40), Auto Tracking

Audio Compression	G.711U,G.711A
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR,NAS(NFS) Network
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API,SDK
User/Host	Up to 32 users. 2 user levels: administrator and common user
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 200°/s Preset speed: 300°/s
Tilt Range	-15° ~ 90° (auto reverse)
Tilt Speed	0.1°/s ~ 200°/s Preset speed: 240°/s
Number of Presets	1024
Preset Patrol	16 patrols, up to 64 presets for each patrol
Patrol Stay Time	15s~1800s
Home Position	Support
Audio I/O	1/1
Alarm I/O	2/1
Serial Port	1 RS485
Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC
Power	AC 24V±25%, DC 24V±25%, PoE+ (IEEE802.3 at) Power consumption: Max 25W
Dimensions (Ø x H)	Ø227 x 384.8mm (Ø8.9" x 15.1")
Weight	5.28kg(11.64lb)
Working Environment	-40°C ~70°C (-40°F ~ 158°F) , Humidity: ≤95% RH (non-condensing)
Surge protection	6KV
Reset button	Support
Protection	Ingress Protection: IP66 Vandal Resistant: N/A

Dimensions



WWW.DIESPI.IR
۰۵۱ - ۳۶۱۱۲۲۶۶
۰۵۱ - ۳۶۱۱۲۲۹۹
آدرس دفتر مرکزی
مشهد - بلوار سجاد - خیابان حامد جنوبی ۱۴ - نبش عمید ۱۳ - پلاک ۳۷ - واحد ۲