

IPC-P1A2W-I50S

2MP VF Network IR Bullet Camera



Accessories

Control

NVR

Network Camera

Video Decoder

- قابلیت روز و شب
- IR هوشمند تا 50 متر
- کاهنده نویز دیجیتال 3D
- 120 WDR دسیبل

- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16

قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- پشتیبانی از POE
- دمای کارکرد -35 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/2.8", 2.0megapixel, progressive scan, CMOS					OSD	Up to 8 OSDs
Lens	2.8-12mm,AF automatic focusing and motorized zoom lens					Privacy Mask	Up to 8areas
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	ROI	Up to 8areas
	2.8	45	18	9	4.5	Motion Detection	Up to 4 areas
	12	192.9	77.1	38.6	19.3	Smart Features	Audio detection, Cross line, intrusion, object left, object removed,People Counting, Face Capture
Angle of View (H)	94.0° ~ 28°					Audio Compression	G.711
Angle of View (V)	56.7°~14.4°					Two-way audio	Supported
Angle of View (O)	122.2°~34.4°					Suppression	Supported
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°		Rotate: 0° ~ 360°	Sampling Rate	8KHZ
Shutter	Auto/Manual, 1~ 1/100000s					Edge Storage	Micro SD, up to 256GB
Minimum Illumination	Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR on					Network Storage	ANR
Day/Night	IR-cut filter with auto switch (ICR)					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Digital noise reduction	2D/3D DNR					Compatible Integration	ONVIF(Profile S, Profile G, Profile T), API
S/N	>52dB						Audio I/O
IR Range	Up to 50m (164ft) IR range					Alarm I/O	1/1
Defog	Digital Defog					Network	1 RJ45 10M/100M Base-TX Ethernet
WDR	120dB					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 9W
Video Compression	Ultra 265, H.265, H.264, MJPEG					Dimensions (L × W × H)	253.4 ×86 ×71.7mm (9.98" × 3.4" × 2.8")
H.264 code profile	Baseline profile, Main Profile, High Profile					Weight	1.0kg (2.2lb)
Frame Rate	Main Stream:2MP (1920*1080), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream:D1 (720*576), Max30fps					Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
9:16 Corridor Mode	Supported					Ingress Protection	IP67
HLC	Supported						
BLC	Supported						

Dimensions

