

# IPC-P2F4W-I50S

4MP LightHunter Deep Learning Vandal-resistant Dome Network Camera



### قابلیت های کلیدی


- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- OSD قابل تنظیم
- قابلیت شب و روز
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

## Specifications

Sensor	1/2.7", 4.0 megapixel, progressive scan, CMOS			
Lens	2.8-4.0mm@F1.6			
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)
	4.0	63.0(206.7ft)	25.2(82.7ft)	12.6(41.7ft)
Angle of View (H)	95.8°-78.9°			
Angle of View (V)	51.5°-40.8°			
Angle of View (D)	124.5°-97.0°			
Adjustment angle	Pan: 0°-355°		Tilt: 0°-80°	Rotate: 0°-355°
Shutter	Auto/Manual, 1 - 1/100000s			
Minimum Illumination	Colour:0.003lux (F1.6, AGC ON) 0 lux with IR			
WDR	120dB			
Day/Night	IR-cut filter with auto switch (ICR)			
IR Range	Up to 50m (164 ft) IR range			
Wavelength	850nm			
IR On/Off Control	Auto/Manual			
Defog	Digital Defog			
Video Compression	Ultra 265, H.265, H.264, MJPEG			
Frame Rate	Main Stream: 4MP(2688*1520),Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps			
Video Bit Rate	128 Kbps-16 Mbps			
ROI	Supported			
Privacy Mask	Up to 8 areas(8 blacks/8 mosaics)			
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2			
Digital noise reduction	2D/3D DNR			
Smart IR	Support			
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise			
HLC/BLC	Support			
Smart intrusion prevention	Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection			
Recognition	Face capture Support face detection masked area			
Statistical Analysis	People counting, support people flow counting and crowd density monitoring			

Basic Detection	Motion detection, Audio detection, Tampering alarm
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	G.711U,G.711A
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR,NAS(NFS)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	EZStation EZLive EZview
Audio I/O	Audio cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 output: impedance 600Ω; amplitude 2V [p-p]
Network	1 * RJ45 10M/100M Base-TX Ethernet
Certifications	CE: EN 60950-1 UL: UL 60950-1 FCC: FCC Part 15
Power	DC12V(±25%), PoE(IEEE 802.3af) Power consumption: Max 5W
Dimensions (Ø x H)	Ø109 x 81mm(Ø4.3" x 3.2")
Weight	0.43kg(0.95lb)
Working Environment	-40°C - 60°C (-40°F - 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
Surge protection	2KV
Vandal Resistant	IK10
Ingress Protection	IP67

## Dimensions



68

