

IPC-P2A5W-I50S

5MP LightHunter Deep Learning Vandal-resistant Dome Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- قابلیت شب و روز
- IR هوشمند 50 تا 80 متر
- کاهنده نویز دیجیتال 3D

Specifications

| | | | | | |
|-------------------------|--|----------------|---------------|---------------|-----------------|
| Sensor | 1/2.7", 5.0 megapixel, progressive scan, CMOS | | | | |
| Lens | 2.7-13.5mm@F1.2, AF automatic focusing and motorized zoom lens | | | | |
| Iris | Auto aperture | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 2.7 | 70.9(232.5ft) | 28.4(93.0ft) | 14.2(46.5ft) | 7.1(23.3ft) |
| | 13.5 | 247.5(812.0ft) | 99.0(324.8ft) | 49.5(162.4ft) | 24.8(81.2ft) |
| Angle of View (H) | 26.8°-93.1° | | | | |
| Angle of View (V) | 20.7°-66.0° | | | | |
| Angle of View (D) | 31.6°-121.0° | | | | |
| Shutter | Auto/Manual, 1 - 1/100000s | | | | |
| Adjustment angle | Pan: 0°-355° | | Tilt: 0°-80° | | Rotate: 0°-355° |
| Minimum Illumination | Colour:0.002lux (F1.2, AGC ON) 0 lux with IR | | | | |
| WDR | 120dB | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| IR Range | 50-80m IR range | | | | |
| Wavelength | 850nm | | | | |
| IR On/Off Control | Auto/Manual | | | | |
| Defog | Digital Defog | | | | |
| Frame Rate | Main Stream: 5MP(2592*1944), Max 20fps; 4MP(2560*1440), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps | | | | |
| Video Bit Rate | 128 Kbps-16 Mbps | | | | |
| ROI | Supported | | | | |
| Video stream | Triple streams | | | | |
| OSD | Up to 8 OSDs | | | | |
| Privacy Mask | Up to 8 areas(8 blacks/8 mosaics) | | | | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 | | | | |
| Digital noise reduction | 2D/3D DNR | | | | |
| Smart IR | Support | | | | |
| Flip | Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise | | | | |
| HLC | Support | | | | |

| | |
|------------------------|--|
| BLC | Support |
| Smart Features | Deep learning, Cross line, intrusion detection, Enter area, Leave area, Face Capture (maximum 8), People flow counting and Crowd density monitoring, Audio detection, object removed, object left behind |
| General Function | Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication |
| Audio Compression | 6.711U,6.711A |
| Two way audio | Supported |
| Suppression | Supported |
| Sampling Rate | 8KHZ |
| Edge Storage | Micro SD, up to 256 GB |
| Network Storage | ANR,NAS(NFS) |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API |
| Web Browser | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below |
| Audio I/O | 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 output: impedance 600Ω; amplitude 2V [p-p] |
| Alarm I/O | 1/1 |
| Network | 1 x RJ45 10M/100M Base-TX Ethernet |
| Power | Power consumption: Max 8W Support overcurrent protection, Input short circuit protection |
| Dimensions (Ø x H) | Ø148.0 x 111.4mm (Ø5.8" x4.4") |
| Weight | 0.93kg(2.05lb) |
| Working Environment | -30°C - 60°C [-22°F - 140°F], Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -40°C - 70°C [-40°F - 158°F], Humidity: ≤95% RH (non-condensing) |
| Surge protection | 6KV |
| Vandal Resistant | IK10 |
| Ingress Protection | IP67 |

Dimensions

