

# IPC-E2F4D-I30

4MP Vandal-resistant Network IR Fixed Dome Camera



Accessories

Control

NVR

Network Camera

Video Decoder

## قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند تا 30 متر
- کاهش نویز دیجیتال 3D
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 2 حالت
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI

## Specifications

|                         |  |            |             |               |              |                        |  |
|-------------------------|--|------------|-------------|---------------|--------------|------------------------|--|
| sensor                  | 1/3", progressive scan, 4.0 megapixel, CMOS    |            |             |               |              | HLC                    | Supported  |
| Lens                    | 2.8mm@F2.0                                     |            |             |               |              | BLC                    | Supported  |
| DORI Distance           | Lens (mm)                                      | Detect (m) | Observe (m) | Recognize (m) | Identify (m) | OSD                    | Up to 4 OSDs   |
|                         | 2.8  | 42         | 16.8        | 8.4           | 4.2          | Privacy Mask           | Up to 8 areas  |
| Angle of View (H)       | 104.4°   |            |             |               |              | ROI                    | Up to 2 areas  |
| Angle of View (V)       | 54.4°  |            |             |               |              | Motion Detection       | Up to 4 areas  |
| Angle of View (O)       | 135.7°   |            |             |               |              | Smart Features         | intrusion, Human body detection  |
| Adjustment angle        | Pan 0° - 360°                                  |            |             |               |              | Intrusion              | Enter and loiter in a pre-defined virtual region   |
| Shutter                 | Auto/Manual, 1 ~ 1/100000s                     |            |             |               |              | Protocols              | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS |
| Minimum Illumination    | Colour: 0.03Lux (F2.0, AGC ON)<br>0Lux with IR |            |             |               |              | Compatible Integration | ONVIF (Profile S, Profile T), API  |
| Day/Night               | IR-cut filter with auto switch (ICR)           |            |             |               |              | Network                | 1 RJ45 100M Base-TX Ethernet   |
| Digital noise reduction | 2D/3D DNR                                      |            |             |               |              | Power                  | DC 12V±25%, PoE (IEEE 802.3af)<br>Power consumption: Max 4W  |
| S/N                     | >52dB  |            |             |               |              | Dimensions (ø x H)     | Ø109 x 81mm (Ø4.3" x 3.2")   |
| IR Range                | Up to 30m (98ft) IR range                      |            |             |               |              | Weight                 | 0.45kg (0.99lb)  |
| Defog                   | Digital Defog                                  |            |             |               |              | Working Environment    | -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)   |
| WDR                     | 100dB  |            |             |               |              | Ingress Protection     | IP67   |
| Video Compression       | Ultra 265, H.265, H.264, MJPEG                 |            |             |               |              | Vandal Resistant       | IK10   |
| H.264 code profile      | Baseline profile, Main Profile                 |            |             |               |              |                        |  |
| Frame Rate              | Main Stream: 4MP (2592*1520), Max 20fps;       |            |             |               |              |                        |  |
|                         | Sub Stream: 720P (1280*720), Max 20fps;        |            |             |               |              |                        |  |
|                         | Third Stream: D1 (720*576), Max 20fps          |            |             |               |              |                        |  |

## Dimensions

