

# IPC-P2A4W-I30S

## 4MP WDR VF Vandal-resistant IR Dome Network Camera



### قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند تا 30 متر
- WDR 120 دسیبل
- کاهنده نویز دیجیتال 3D
- لنز موتورایز برای زوم از راه دور
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- پشتیبانی از POE
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16

### Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS					DSD	Up to 8 OSDs
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens					Privacy Mask	Up to 8 areas
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	ROI	Up to 8 areas
	2.8	63	25.2	12.6	6.3	Motion Detection	Up to 4 areas
Angle of View (H)	12	270	108	54	27	Audio Compression	G.711
	91.0° - 27°		Tilt: 0° - 90°		Rotate: 0° - 360°	Two-way audio	Supported
Angle of View (V)	54.4° - 13.7°					Suppression	Supported
Angle of View (O)	118.3° - 33.2°					Sampling Rate	8KHZ
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°		Rotate: 0° - 360°	Edge Storage	Micro SD, up to 256GB
Shutter	Auto/Manual, 1 - 1/100000s					Network Storage	ANR
Minimum Illumination	Colour: 0.005Lux (F1.4, AGC ON) 0Lux with IR					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Day/Night	IR-cut filter with auto switch (ICR)					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Digital noise reduction	2D/3D DNR					Audio I/O	Audio cable Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
S/N	>55 dB					Alarm I/O	1/1
IR Range	Up to 30m (98ft) IR range					Network	1 RJ45 10M/100M Base-TX Ethernet
Defog	Digital Defog					Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
WDR	120dB					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.2W
Video Compression	Ultra 265, H.264, MJPEG					Dimensions (D x H)	Φ148 x 111.3mm (Ø5.8" x 4.4")
H.264 code profile	Baseline profile, Main Profile, High Profile					Weight	0.75kg (1.7lb)
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; 4MP (2560*1440), Max 25fps;					Working Environment	-40°C - 60°C (-40°F - 140°F), Humidity: ≤95% RH (non-condensing)
	3MP (2048*1520), Max 30fps;					Ingress Protection	IP67
	Sub Stream: 2MP (1920*1080), Max 30fps;					Vandal Resistant	IK10
HLC	Third Stream: D1 (720*576), Max 30fps					Reset Button	Supported
	Supported						
BLC	Supported						
9:16 Corridor Mode	Supported						

### Dimensions

