

IPC-E3F2D-I30/D

2MP Fixed Dome Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	43.4	17.4	8.7	4.3
Angle of View (H)	106.7°				
Angle of View (V)	57.1°				
Angle of View (D)	115.7°				
Shutter	Auto/Manual, 1 - 1/100000s				
Adjustment angle	Pan: 0° - 360°	Tilt: 0° - 80°		Rotate: 0° - 360°	
	Minimum Illumination				
Colour: 0.01Lux (F2.0, AGC ON)					
0Lux with IR on					
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	30-50m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	100dB				
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; 128 Kbps-16 Mbps				
Video Bit Rate	128 Kbps-16 Mbps				
9:16 Corridor Mode	Supported				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Smart Features	N/A				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Supported				
Flip	Normal/Vertical/Horizontal/180°				
Dewarping	N/A				
HLC	Supported				
BLC	Supported				
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP				
Compatible Integration	API				
Web Browser	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+				
Network	10/100M Base-TX Ethernet				
Power	DC 12V±25%, PoE (IEEE 802.3af)				
	Power consumption: Max 5.0W				
Dimensions (D x H)	Φ118 x 95mm (Φ4.6" x 3.8")				
Net Weight	0.29kg (0.64lb)				
Material	Metal + Plastic				
Working Environment	-30°C - 60°C [-22°F - 140°F], Humidity: ≤95% RH (non-condensing)				
Storage Environment	-30°C - 60°C [-22°F - 140°F], Humidity: ≤95% RH (non-condensing)				
Surge Protection	4KV				
Ingress Protection	IP67				
Reset Button	N/A				

Dimensions

