

IPC-P1A8W-I50S

8MP VF Network IR Bullet Camera



Accessories

Control

NVR

Network Camera

Video Decoder

قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -35 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- OSD قابل تنظیم
- قابلیت روز و شب
- IR هوشمند تا 50 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز
- 120WDR دسیبل
- Ultra 256, H.265, H.264, MJPEG

Specifications

Sensor	1/2", 8.0 megapixel, progressive scan, CMOS					OSD	Up to 8 OSDs
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens					Privacy Mask	Up to 8 areas
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	ROI	Up to 8 areas
	2.8	63	25.2	12.6	6.3	Motion Detection	Up to 4 areas
	12	270	108	54	27	Smart Features	Audio detection, Cross line, intrusion, object left, object removed, People Counting, Face Capture
Angle of View (H)	114.8° - 47.3°					Audio Compression	G.711
Angle of View (V)	75.3° - 20.4°					Two-way audio	Supported
Angle of View (D)	141.2° - 55.8°					Suppression	Supported
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°		Rotate: 0° - 360°	Sampling Rate	8KHZ
Shutter	Auto/Manual, 1 - 1/100000s					Edge Storage	Micro SD, up to 256GB
Minimum Illumination	Colour: 0.001Lux (F1.5, AGC ON) 0Lux with IR on					Network Storage	ANR
Day/Night	IR-cut filter with auto switch (ICR)					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Digital noise reduction	2D/3D DNR						Compatible Integration
S/N	>52dB					Audio I/O	Audio cable Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
IR Range	Up to 50m (164ft) IR range						Alarm I/O
Defog	Digital Defog					Network	1 RJ45 10M/100M Base-TX Ethernet
WDR	120dB					Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
Video Compression	Ultra 265, H.265, H.264, MJPEG					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 9W
Frame Rate	Main Stream: 8MP (3840*2160), Max 20fps; 5MP (2592*1944), Max 30fps; 5MP (2944*1656), Max 30fps; 4MP (2560*1440), Max 30fps; 2MP (1920*1080), Max 30fps;						Dimensions (L x W x H)
	Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps					Weight	1.0kg (2.2lb)
	9:16 Corridor Mode	Supported					Working Environment
HLC	Supported					Ingress Protection	IP67
BLC	Supported						

Dimensions

