

IPZ-P4425W-I100S

4MP 25x Lighthunter Network PTZ Dome Camera



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- زوم اپتیکال تا 25 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق تر و سریع
- IR هوشمند تا 100 متر
- رزولوشن 4 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +70 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- بدنه ضد ضربه با استاندارد IK10

Specifications

Sensor	1/2.8", 4.0 megapixel, progressive scan, CMOS				Audio Compression	6.711U, 6.711A
Minimum Illumination	Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR				Two-way Audio	Support
Day/Night	IR-cut filter with auto switch (ICR)				Suppression	Support
Shutter	Auto/Manual, 1 - 1/100000s				Sampling Rate	8 kHz
WDR	120dB				Edge Storage	Micro SD, up to 256 GB
S/N	>56dB				Network Storage	ANR, NAS (NFS)
Lens type	4.8 - 120mm, AF automatic focusing and motorized zoom lens				Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Digital Zoom	16				Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
Optical Zoom	25				User/Host	Up to 32 users. 2 user levels: administrator and common user
Iris	Auto; F1.5 - F3.8				Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Angle of View (H)	52.20°-2.74°				Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Angle of View (V)	30.81°-1.54°				Pan Range	360° (endless)
Angle of View (D)	64.20°-3.23°				Pan Speed	0.1°/s ~ 200°/s Preset speed: 240°/s
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Tilt Range	-15° - 90° (auto reverse)
					Tilt Speed	0.1°/s ~ 200°/s Preset speed: 200°/s
IR Range	Up to 100m IR range				Number of Presets	1024
Wavelength	850nm				Preset Patrol	16 patrols, up to 64 presets for each patrol
IR On/Off Control	Auto/Manual				Patrol Stay Time	15s-1800s
Video Compression	Ultra 265, H.265, H.264, MJPEG				Home Position	Support
Frame Rate	Main Stream: 4MP(2688*1520), Max 30fps;				Audio I/O	1/1
	Sub Stream: 2MP (1920*1080), Max 30fps;				Alarm I/O	2/1
	Third Stream: DL (720*576), Max 30fps;				Serial Port	1 RS485
Video Bit Rate	128 Kbps-16 Mbps				Network	1 * RJ45 10M/100M Base-TX Ethernet
ROI	Support				Video Output	1 BNC
OSD	Up to 8 OSDs				Power	DC12V(±25%, 3A), PoE+(IEEE 802.3at)
Privacy Mask	24 areas, up to 4 areas per scene				Weight	Power consumption: MAX 21W 3.05kg(6.72lb)
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				Working Environment	-40°C-70°C(-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
Digital noise reduction	2D/3D DNR				Surge Protection	6KV
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				Reset Button	Support
HLC	Support				Protection	Ingression protection: IP67 Vandal resistant: IK10
BLC	Support					
Defog	Digital Defog					
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication					
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40), Auto Tracking					

Dimensions



98

