

IPC-E1F4D-I30 4.0mm/R

4MP Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- OSD قابل تنظیم
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

- پایه قابل تنظیم 3 حالت
- دارای میکروفون داخلی
- پشتیبانی از ROI

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/3", progressive scan, CMOS				
Lens	4.0mm@F2.1				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	90.0	36.0	18.0	9.0
Angle of View (H)	79.0°				
Angle of View (V)	42.3°				
Angle of View (D)	85.1°				
Adjustment angle	Pan: 0° - 360°	Tilt: 0° - 90°	Rotate: 0° - 360°		
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.02Lux (F2.1, AGC ON) 0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	30-50m IR range				
Defog	Digital Defog				
WDR	100dB				
Audio Compression	6.711				
Suppression	Supported				
Sampling Rate	8KHZ				
Video Compression	Ultra 265, H.265, H.264				
Frame Rate	Main Stream: 4MP (2560*1440), Max 20fps; 3MP (2304*1296), Max 20fps; 1080P (1920*1080), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;				

HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Basic Detection	Audio Detection
Protocols	IPV4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP, RTMP
Compatible Integration	ONVIF (Profile S, Profile T), API
Network	10/100M Base-TX Ethernet
Built-in Mic	Supported
Power	DC 12V±25%, PoE Power consumption: Max 3.5W
Dimensions (L x W x H)	144 x 60 x 65mm (5.6" x 2.4" x 2.6")
Weight	0.17kg (0.37lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67
Reset Button	N/A

Dimensions

